

ProfiCut

Series H 8607 and HB 8607



**THE POWERFUL HAND CUTTING TORCH
FOR FLAME CUTTING AND FLAME GOUGING**

ProfiCut H and HB 8607-A/PMYF

The new range of **ProfiCut H and HB** heavy duty hand cutting torches for nozzle-mix (3-seat) nozzles continues the tradition of Messer torches with the quality and reliability which is synonymous with Messer. **ProfiCut H and HB** is a proven design incorporating the latest technical features necessary to meet the ever-changing applications and requirements of the hand cutting market. Its ergonomic and modern functional design permits steady, effortless control by hand and its balanced weight enables the operator positive and comfortable working conditions for a continuous operation.

The cutting and gouging torch range **ProfiCut H and HB** is the low cost alternative for high quality value.



ProfiCut H 8607-A/PMY



ProfiCut HB 8607-A/PMY

- Designed in accordance to the most current internationally recognized standards EN ISO, BSP, CGA and NFS
- Manufactured under the quality management system of EN ISO 9001.
- 100% tested before despatch.
- Principally designed for general workshop cutting up to 300 mm / 14 inches capacity.
- Torch length of 510 mm / 20 inches ensures optimal balanced weight distribution increasing operator efficiency and comfort.
- 1050 g / 2.3 lbs weight enables controlled movements and makes it ideally suited for a wide range of industrial applications.
- 90° solid forged head withstands toughest working conditions.
- Large cross-sectional areas enable high gas flow and ensures that the required oxygen and fuel flow gas rates, even on heavy duty applications with low gas pressures, are still maintained.
- In-plane parallel arranged stainless steel tubes and rugged design ensures maximum strength.
- Suitable for use with all types of fuel gases simply by changing the cutting nozzle.
- Adjustable gland packed gas valves allow precise and sensitive adjusting as well as accurate control of the flame.
- Colour coded adjusting valves for easy identification.
- Top mounted stainless steel lever with the benefit of a unique cutting oxygen flow valve operated by the cutting lever acts indirectly to bring in the oxygen stream. This important feature gives a true "bleed characteristic" to create splash free starts and progressive, controlled piercing and the smoothest possible cutting conditions.
- Cutting oxygen lever incorporates a locking lug for maximum operator comfort.
- Modular design reduces maintenance cost and downtime.

ProfiCut H Model	Part No.	Standard	Gas Service	Cutting Rang [mm]/[inch]	Oxygen/ Fuel Gas Ident. Colour	Nozzle Connection	Inlet Connection Oxygen	Inlet Connection Fuel Gas		
H 8607E	716.06004	DIN	A/PMYF	3-300 / 1/8-12	blue/red	Intern. 30°	G 1/4-RH(M)	G 3/8-LH(M)		
HB 8607E	716.07124						G 3/8-RH(M)	G 3/8-LH(M)		
H 8607B	716.06005	BSP					green/red	9/16"NF-RH(M)	9/16"NF-LH(M)	
HB 8607B	716.07125							M 16x1,5-RH(M)	M 16x1,5-LH(M)	
H 8607U	716.06006	CGA			blue/red		G 1	Intern. 30°	5/8 UNF-RH(M)	5/8 UNF-LH(M)
HB 8607U	716.07126									
H 8607F	716.06007	NFE			AS					
HB 8607F	716.07127									
H 8607FG	716.06008									
HB 8607FG	716.07128									
H 8607AS	716.06135									
HB 8607AS	716.07129									

MESSER 
Cutting Systems

Edition 01/11
Subject to change without notice COM
© Messer Cutting Systems GmbH
® registered trademark of
Messer Cutting Systems GmbH
Oxyfuel Technology

Messer Cutting Systems GmbH
Oxyfuel Technology
Otto-Hahn Straße 2 - 4
D-64823 Groß-Umstadt Germany
Phone +49 6078 787-0
Fax +49 6078 787-150
E-mail: info@messer-cs.de
Internet: www.messer-cs.de

Your authorized Messer distributor:

